Chapter NR 253

COPPER FORMING

NR 253.01	Purpose.	NR 253.12	Effluent limitations representing the degree of effluent reduction
NR 253.02	Applicability.		attainable by the application of the best available technology eco-
NR 253.03	General definitions.		nomically achievable.
NR 253.04	Monitoring and reporting requirements.	NR 253.13	New source performance standards.
NR 253.05	Compliance dates.	NR 253.14	Pretreatment standards for existing sources. Except as provided in ss.
Subchapter I	— The Copper Forming Subcategory		NR 211.13 and 211.14, any existing source subject to this sub- chapter which introduces pollutants into a POTW shall comply
NR 253.10	Applicability; description of the copper forming subcategory.		
NR 253.11	Effluent limitations representing the degree of effluent reduction	NID 252 15	with ch. NR 211 and achieve the following PSES:
	attainable by the application of the best practicable control	NR 253.15	Pretreatment standards for new sources.
	technology currently available.		

NR 253.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the copper forming point source category and its subcategories.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

- NR 253.02 Applicability. This chapter applies to discharges resulting from hot rolling, cold rolling, drawing, extrusion, and forging of copper and copper alloys and the associated ancillary operations. This chapter does not apply to the forming of precious metals, which is regulated by 40 CFR 471, or the casting of copper or copper alloys, which is regulated by ch. NR 256. History: Cr. Register, May, 1989, No. 401, eff. 6–1–89.
- NR 253.03 General definitions. The following definitions are applicable to the terms used in this chapter. Definitions of other terms and abbreviations are set forth in ss. NR 205.03, 205.04 and 211.03.
- (1) "Alkaline cleaning bath" means a bath consisting of an alkaline cleaning solution through which a workpiece is processed.
- (2) "Alkaline cleaning rinse" means a rinse following an alkaline cleaning bath through which a workpiece is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- **(3)** "Alkaline cleaning rinse for forged parts" means a rinse following an alkaline cleaning bath through which a forged part is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- **(4)** "Ancillary operation" means an operation, such as surface and heat treatment, hydrotesting, sawing, and surface coating, associated with a primary forming operation.
- **(5)** "Annealing with oil" means the use of oil to quench a workpiece as it passes from an annealing furnace.
- **(6)** "Annealing with water" means the use of a water spray or bath, of which water is the major constituent, to quench a workpiece as it passes from an annealing furnace.
- (7) "Beryllium copper alloy" means any copper alloy that is alloyed to contain 0.10% or greater beryllium.
- **(8)** "Cold rolling" means the process of rolling a workpiece below the recrystallization temperature of the copper or copper alloy.
- **(9)** "Drawing" means pulling the workpiece through a die or succession of dies to reduce the diameter or alter its shape.
- (10) "Existing source" means any point source, except for a new source as defined in sub. (16), from which pollutants may be discharged either into waters of the state or into a publicly owned treatment works.
- (11) "Extrusion" means the application of pressure to a copper workpiece, forcing the copper to flow through a die orifice.

- **(12)** "Extrusion heat treatment" means the spray application of water to a workpiece for the purpose of heat treatment immediately following extrusion.
- (13) "Hot rolling" means the process of rolling a workpiece above the recrystallization temperature of the copper or copper alloy.
- (14) "Heat treatment" means the application of heat to or the removal of heat from a workpiece to change the physical properties of the metal.
- (15) "Miscellaneous waste stream" means hydrotesting, sawing, surface milling, and maintenance wastestreams when they are related to the forming of copper.
- (16) "New source", as defined for new source performance standards and pretreatment standards for new sources, means any point source for which construction commenced after November 12, 1982 and from which pollutants are or may be discharged directly to the waters of the state or to a publicly owned treatment works.
- (17) "Off kilogram" and "off pound" mean the mass of copper or copper alloy removed from a forming or ancillary operation at the end of a process cycle for transfer to a different machine or process.
- (18) "Pickling bath" means a chemical bath, other than an alkaline cleaning bath, through which a workpiece is processed.
- (19) "Pickling fume scrubber" means an air pollution control device which removes particulates and fumes from air above a pickling bath by entraining the pollutants in water.
- (20) "Pickling rinse" means a rinse, other than an alkaline cleaning rinse, through which a workpiece is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- **(21)** "Pickling rinse for forged parts" means a rinse, other than an alkaline cleaning rinse, through which forged parts are processed. A rinse consisting of a series of tanks is considered as a single rinse.
- **(22)** "Precious metals" means gold, platinum, palladium, silver, and their alloys when the alloy contains 30% or greater percent by weight of precious metals.
- (23) "Primary forming operation" means hot rolling, cold rolling, drawing, extrusion, and forging of copper and copper alloys.
- (24) "Rolling" means reducing the thickness or diameter of a workpiece by passing it between rollers.
- (25) "Solution heat treatment" means introducing a workpiece into a quench bath for purposes of heat treatment.
- (26) "Spent lubricant" means water or an oil and water mixture which has been used in forming operations to reduce friction, heat, and wear and which is discharged.

- (27) "Surface coating" means the process of coating a copper workpiece, as well as the associated surface washing and flattening.
- (28) "Total toxic organics" and "TTO" mean the sum of the masses or concentrations of each of the following organic compounds which is found at a concentration greater than 0.010 mg/l: anthracene

benzene chloroform

2,6–dinitrotoluene

ethylbenzene

methylene chloride

naphthalene

N-nitrosodiphenylamine

phenanthrene

toluene

1,1,1-trichloroethane trichlorethylene.

(29) "Tumbling or burnishing" means polishing, deburring, removing sharp corners, and generally smoothing parts for both cosmetic and functional purposes and washing the finished parts and cleaning the abrasive media.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.04 Monitoring and reporting requirements. The following special monitoring and reporting requirements apply to all facilities subject to this chapter:

- (1) The "monthly average" regulatory values shall be the basis for the monthly average discharge in direct discharge permits and for pretreatment standards. Compliance with the monthly discharge limit is required regardless of the number of samples analyzed and averaged.
- (2) As an alternate monitoring procedure for TTO, indirect dischargers may monitor for oil and grease and meet the alternate monitoring standards for oil and grease established for PSES and PSNS. Any indirect discharger meeting the alternate monitoring standards shall be considered to meet the TTO standard.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

- **NR 253.05 Compliance dates. (1)** Any existing source subject to this chapter which discharges to waters of the state shall achieve:
- (a) The effluent limitations representing BPT by July 1, 1977; and $\,$
- (b) The effluent limitations representing BAT by July 1, 1984.
- (2) Any new source subject to this chapter which discharges to waters of the state shall achieve NSPS at the commencement of discharge.
- **(3)** Any existing source subject to this chapter which introduces process wastewater pollutants into a POTW shall achieve PSES by August 15, 1986.
- **(4)** Any new source subject to this chapter which introduces process wastewater pollutants into a POTW shall achieve PSNS at the commencement of discharge.

History: Cr. Register, May, 1989, No. 401, eff. 6–1–89.

Subchapter I — The Copper Forming Subcategory

NR 253.10 Applicability; description of the copper forming subcategory. This subchapter applies to the discharge of pollutants to waters of the state and the introduction of pollutants into POTWs from the forming of copper and copper alloys except beryllium copper alloys.

History: Cr. Register, May, 1989, No. 401, eff. 6–1–89.

NR 253.11 Effluent limitations representing the degree of effluent reduction attainable by the applica-

tion of the best practicable control technology currently available. Except as provided in 40 CFR 125.30 to 125.32, any existing source subject to this subchapter shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of BPT:

Table 1 Hot Rolling Spent Lubricant

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy hot rolled			
Chromium	0.045	0.018		
Copper	0.195	0.103		
Lead	0.015	0.013		
Nickel	0.197	0.130		
Zinc	0.150	0.062		
Oil and grease	2.060	1.236		
TSS	4.223	2.008		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 2 Cold Rolling Spent Lubricant

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled		
Chromium	0.166	0.068	
Copper	0.720	0.379	
Lead	0.056	0.049	
Nickel	0.727	0.481	
Zinc	0.553	0.231	
Oil and grease	7.580	4.548	
TSS	15.539	7.390	
pН	(1)	(1)	

Table 3
Drawing Spent Lubricant (1)

Drawing Spent Eubricant (1)				
BPT	BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn			
Chromium	0.037	0.015		
Copper	0.161	0.085		
Lead	0.012	0.011		
Nickel	0.163	0.107		
Zinc	0.124	0.051		
Oil and grease	1.700	1.020		
TSS	3.485	1.657		
рН	(2)	(2)		

- (1) These effluent limitations are applicable only to those plants which actually discharge the drawing spent lubricant wastestream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these limitations are neither applicable nor allowable.
- (2) Within the range of 7.5 to 10.0 at all times

Table 4
Solution Heat Treatment

Solution Heat Treatment				
BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated			
Chromium	1.118	0.457		
Copper	4.827	2.541		
Lead	0.381	0.330		
Nickel	4.878	3.227		
Zinc	3.709	1.550		
Oil and grease	50.820	30.492		
TSS	104.181	49.549		
pН	(1)	(1)		

Table 5
Extrusion Heat Treatment

BPT	Effluent Limitation	ıs		
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated			
Chromium	0.00088	0.00036		
Copper	0.003	0.002		
Lead	0.0003	0.00026		
Nickel	0.003	0.002		
Zinc	0.002	0.001		
Oil and grease	0.040	0.024		
TSS	0.082	0.039		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 6
Annealing With Water

8				
BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	pollutant mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water			
Chromium	2.439	1.020		
Copper	10.767	5.667		
Lead	0.850	0.736		
Nickel	10.880	7.197		
Zinc	8.273	3.456		
Oil and grease	113.340	68.004		
TSS	232.347	110.506		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 7
Annealing With Oil

BPT	BPT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy annealed w		
Chromium	0	0	
Copper	0	0	
Lead	0	0	
Nickel	0	0	
Zinc	0	0	
Oil and grease	0	0	
TSS	0	0	
pН	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 8
Alkaline Cleaning Rinse

BPT	BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned			
Chromium	1.854	0.758		
Copper	8.006	4.214		
Lead	0.632	0.547		
Nickel	8.090	5.351		
Zinc	6.152	2.570		
Oil and grease	84.280	50.568		
TSS	172.774	82.173		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 9 Alkaline Cleaning Rinse For Forged Parts

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts alkaline cleaned			
Chromium	5.562	2.275		
Copper	24.019	12.642		
Lead	1.896	1.643		
Nickel	24.272	16.055		
Zinc	18.457	7.711		
Oil and grease	252.840	151.704		
TSS	518.322	246.519		
pН	(1)	(1)		

Table 10 Alkaline Cleaning Bath

5				
BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg(pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned			
Chromium	0.020	0.0084		
Copper	0.089	0.046		
Lead	0.0070	0.0060		
Nickel	0.089	0.059		
Zinc	0.068	0.028		
Oil and grease	0.93	0.56		
TSS	1.91	0.91		
pН	(1)	(1)		

Table 11 Pickling Rinse

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled			
Chromium	1.593	0.651		
Copper	6.881	3.622		
Lead	0.543	0.470		
Nickel	6.954	4.599		
Zinc	5.288	2.209		
Oil and grease	72.440	43.464		
TSS	148.502	70.629		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 12 Pickling Rinse For Forged Parts

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds pounds) of copper of forged parts pickled	per 1,000,000 off— or copper alloy	
Chromium	1.723	0.705	
Copper	7.444	3.918	
Lead	0.587	0.509	
Nickel	7.522	4.975	
Zinc	5.720	2.389	
Oil and grease	78.360	47.016	
TSS	160.638	76.401	
pН	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 13 Pickling Bath

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy pickled	nds per 1,000,000 copper or copper	
Chromium	0.051	0.020	
Copper	0.220	0.116	
Lead	0.017	0.015	
Nickel	0.222	0.147	
Zinc	0.169	0.070	
Oil and grease	2.320	1.392	
TSS	4.756	2.262	
pН	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 14
Pickling Fume Scrubber

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property			
Chromium	0.275	0.112	
Copper	1.189	0.626	
Lead	0.093	0.081	
Nickel	1.201	0.795	
Zinc	0.913	0.381	
Oil and grease	12.520	7.512	
TSS	25.666	12.207	
pH	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 15 Tumbling or Burnishing

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished			
Chromium	0.256	0.104	
Copper	1.107	0.583	
Lead	0.087	0.075	
Nickel	1.119	0.740	
Zinc	0.851	0.355	
Oil and grease	11.660	6.996	
TSS	23.903	11.368	
pH	(1)	(1)	

Table 16 Surface Coating BPT Effluent Limitations

Surface Coming DI I Entractic Emmanders			
	Maximum for any 1 day	monthly average	
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy surface coa		
Chromium	0.326	0.133	
Copper	1.411	0.743	
Lead	0.111	0.096	
Nickel	1.426	0.943	
Zinc	1.084	0.453	
Oil and grease	14.680	8.916	
TSS	30.463	14.488	
pН	(1)	(1)	

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 17 Miscellaneous Waste Streams

TVIISOONAMOO AND TVIISOONAMOO			
BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of calloy formed		
Chromium	0.009	0.003	
Copper	0.041	0.021	
Lead	0.003	0.002	
Nickel	0.041	0.027	
Zinc	0.031	0.013	
Oil and grease	0.436	0.261	
TSS	0.893	0.425	
pН	(1)	(1)	
(1) Within the range of 7.5 to 10.0 at all times			

NR 253.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable. Except as provided in 40 CFR 125.30 to 125.32, any existing source subject to this subchapter shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of BAT:

Table 18 Hot Rolling Spent Lubricant

D. M. D. College			
BAT Effluent Limitations			
Maximum for Maximum for any 1 day monthly average			
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 tant off–pounds) of copper or copper alloy hot rolled		
Chromium	0.045	0.018	
Copper	0.195	0.103	
Lead	0.015	0.013	
Nickel	0.197	0.130	
Zinc	0.150	0.062	

Table 19 Cold Rolling Spent Lubricant

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium	0.166	0.068
Copper	0.720	0.379
Lead	0.056	0.049
Nickel	0.727	0.481
Zinc	0.553	0.231

Table 20 **Drawing Spent Lubricant**

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn		
Chromium	0.037	0.015	
Copper	0.161	0.085	
Lead	0.012	0.011	
Nickel	0.163	0.107	
Zinc	0.124	0.051	

Table 21 Solution Heat Treatment

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated		
Chromium	0.284	0.116	
Copper	1.227	0.646	
Lead	0.096	0.083	
Nickel	1.240	0.820	
Zinc	0.943	0.394	

Table 22 **Extrusion Heat Treatment**

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated			
Chromium	0.00088	0.00036	
Copper	0.003	0.0020	
Lead	0.0003	0.00026	
Nickel	0.003	0.002	
Zinc	0.002	0.001	

⁽¹⁾ Within the range of 7.5 to 10.0 at all times **History:** Cr. Register, May, 1989, No. 401, eff. 6–1–89.

Table 23 Annealing With Water

BAT Effluent Limitations Maximum for Maximum for monthly average any 1 day mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper Pollutant or pollutant property alloy annealed with water Chromium 0.545 0.223 2.356 Copper 1.240 Lead 0.186 0.161 Nickel 2.380 1.574 Zinc 1.810 0.756

Table 24 Annealing With Oil

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of c alloy annealed w		
Chromium	0	0	
Copper	0	0	
Lead	0	0	
Nickel	0	0	
Zinc	0	0	

Table 25 Alkaline Cleaning Rinse

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy alkaline clo		
Chromium	1.854	0.758	
Copper	8.006	4.214	
Lead	0.632	0.547	
Nickel	8.090	5.351	
Zinc	6.152	2.570	

Table 26 Alkaline Cleaning Rinse For Forged Parts

	8	0		
BAT Effluent Limitations				
	Maximum for any 1 day	monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts alkaline cleaned			
Chromium	5.562	2.275		
Copper	24.019	12.642		
Lead	1.896	1.643		
Nickel	24.272	16.055		
Zinc	18.457	7.711		

Table 27 Alkaline Cleaning Bath

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned		
Chromium	0.020	0.0084	
Copper	0.088	0.046	
Lead	0.0070	0.0060	
Nickel	0.089	0.059	
Zinc	0.068	0.028	

Table 28 Pickling Rinse

ricking Kinse			
BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy pickled		
Chromium	0.574	0.235	
Copper	2.481	1.306	
Lead	0.195	0.169	
Nickel	2.507	1.658	
Zinc	1.906	0.796	

Table 29
Pickling Rinse For Forged Parts

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled		
Chromium	1.723	0.705	
Copper	7.444	3.918	
Lead	0.587	0.509	
Nickel	7.522	4.975	
Zinc	5.720	2.389	

Table 30 Pickling Bath

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy pickled	nds per 1,000,000 copper or copper	
Chromium	0.051	0.020	
Copper	0.220	0.116	
Lead	0.017	0.015	
Nickel	0.222	0.147	
Zinc	0.169	0.070	

Table 31 Pickling Fume Scrubber

Picking rune Scrubber			
BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy pickled	nds per 1,000,000 copper or copper	
Chromium	0.275	0.112	
Copper	1.189	0.626	
Lead	0.093	0.081	
Nickel	1.201	0.795	
Zinc	0.913	0.381	

Table 32 Tumbling or Burnishing

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy tumbled or		
Chromium	0.256	0.104	
Copper	1.107	0.583	
Lead	0.087	0.075	
Nickel	1.119	0.740	
Zinc	0.851	0.355	

Table 33 Surface Coating

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy surface coated		
Chromium	0.326	0.133	
Copper	1.411	0.743	
Lead	0.111	0.096	
Nickel	1.426	0.943	
Zinc	1.084	0.453	

Table 34 Miscellaneous Waste Streams

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy formed		
Chromium	0.009	0.003	
Copper	0.041	0.021	
Lead	0.003	0.002	
Nickel	0.041	0.027	
Zinc	0.031	0.013	

History: Cr. Register, May, 1989, No. 401, eff. 6–1–89.

NR 253.13 New source performance standards. The discharge of process wastewater pollutants from any new source subject to this subchapter may not exceed the following NSPS:

Table 35 Hot Rolling Spent Lubricant

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of calloy hot rolled	
Chromium	0.038	0.015
Copper	0.131	0.062
Lead	0.010	0.0092
Nickel	0.056	0.038
Zinc	0.105	0.043
Oil and grease	1.030	1.030
TSS	1.545	1.236
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 36 Cold Rolling Spent Lubricant

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of c alloy cold rolled	
Chromium	0.140	0.056
Copper	0.485	0.231
Lead	0.037	0.034
Nickel	0.208	0.140
Zinc	0.386	0.159
Oil and grease	3.790	3.790
TSS	5.685	4.548
рН	(1)	(1)

Table 37
Drawing Spent Lubricant

Drawing Spent Labricant				
	NSPS			
Pollutant or pollutant property mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy drawn				
Chromium	0.031	0.012		
Copper	0.108	0.051		
Lead	0.0085	0.0076		
Nickel	0.046	0.031		
Zinc	0.086	0.035		
Oil and grease	0.85	0.85		
TSS	1.275	1.020		
pН	(1)	(1)		

Table 38 Solution Heat Treatment

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy heat treated	opper or copper
Chromium	0.239	0.096
Copper	0.826	0.394
Lead	0.064	0.058
Nickel	0.355	0.239
Zinc	0.658	0.271
Oil and grease	6.460	6.460
TSS	9.690	7.752
pH	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 39 Extrusion Heat Treatment

-	NICDC	
	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy heat treated	
Chromium	0.00074	0.00030
Copper	0.0020	0.0010
Lead	0.00020	0.00018
Nickel	0.0010	0.00074
Zinc	0.0020	0.00084
Oil and grease	0.020	0.020
TSS	0.030	0.024
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 40 Annealing With Water

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy annealed wit	pper or copper
Chromium	0.458	0.186
Copper	1.587	0.756
Lead	0.124	0.111
Nickel	0.682	0.458
Zinc	1.264	0.520
Oil and grease	12.400	12.400
TSS	18.600	14.880
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 41 Annealing With Oil

_	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy annealed w	
Chromium	0	0
Copper	0	0
Lead	0	0
Nickel	0	0
Zinc	0	0
Oil and grease	0	0
TSS	0	0
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 42 Alkaline Cleaning Rinse

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy alkaline cleaned	
Chromium	1.559	0.632
Copper	5.393	2.570
Lead	0.421	0.379
Nickel	2.317	1.559
Zinc	4.298	1.769
Oil and grease	42.140	42.140
TSS	63.210	50.568
pН	(1)	(1)

Table 43 Alkaline Cleaning Rinse For Forged Parts

Tilkumie Cleuming Rinse I of I orged I arts		
	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy alkaline cle	
Chromium	4.677	1.896
Copper	16.181	7.711
Lead	1.264	1.137
Nickel	6.953	4.677
Zinc	12.894	5.309
Oil and grease	126.420	126.420
TSS	189.630	151.704
pН	(1)	(1)

Table 44
Alkaline Cleaning Bath

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy alkaline cle	
Chromium	0.017	0.0070
Copper	0.059	0.028
Lead	0.0046	0.0042
Nickel	0.025	0.017
Zinc	0.047	0.019
Oil and grease	0.46	0.46
TSS	0.70	0.56
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 45 Pickling Rinse

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
-	, ,	, ,
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy pickled	nds per 1,000,000 opper or copper
Chromium	0.216	0.087
Copper	0.748	0.356
Lead	0.058	0.052
Nickel	0.321	0.216
Zinc	0.596	0.245
Oil and grease	5.850	5.850
TSS	8.775	7.020
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 46
Pickling Rinse For Forged Parts

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of c alloy forged part	
Chromium	0.649	0.263
Copper	2.246	1.070
Lead	0.175	0.157
Nickel	0.965	0.649
Zinc	1.790	0.737
Oil and grease	17.550	17.550
TSS	26.325	21.060
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 47 Pickling Bath

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy pickled	nds per 1,000,000 opper or copper
Chromium	0.042	0.017
Copper	0.148	0.070
Lead	0.011	0.010
Nickel	0.063	0.042
Zinc	0.118	0.048
Oil and grease	1.160	1.160
TSS	1.740	1.392
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 48 Pickling Fume Scrubber

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy pickled	
Chromium	0.231	0.093
Copper	0.801	0.381
Lead	0.062	0.056
Nickel	0.344	0.231
Zinc	0.638	0.262
Oil and grease	6.260	6.260
TSS	9.390	7.512
pH	(1)	(1)

Table 49 Tumbling or Burnishing

<u> </u>	NSPS	<u> </u>
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy tumbled or burnished	
Chromium	0.215	0.087
Copper	0.746	0.355
Lead	0.058	0.052
Nickel	0.320	0.215
Zinc	0.594	0.244
Oil and grease	5.830	5.830
TSS	8.745	6.996
pH	(1)	(1)

Table 50 Surface Coating

Surface County		
	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy surface coate	pper or copper
Chromium	0.274	0.111
Copper	0.951	0.453
Lead	0.074	0.066
Nickel	0.408	0.274
Zinc	0.757	0.312
Oil and grease	7.430	7.430
TSS	11.145	8.916
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 51 Miscellaneous Waste Streams

Wiscenancous Waste Streams		
	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pound off–pounds) of co alloy formed	
Chromium	0.008	0.003
Copper	0.027	0.013
Lead	0.0021	0.0019
Nickel	0.011	0.008
Zinc	0.022	0.009
Oil and grease	0.218	0.218
TSS	0.327	0.261
pH	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

History: Cr. Register, May, 1989, No. 401, eff. 6–1–89.

NR 253.14 Pretreatment standards for existing sources. Except as provided in ss. NR 211.13 and 211.14, any

existing source subject to this subchapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSES:

Table 52 Hot Rolling Spent Lubricant

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy hot rolled	
Chromium	0.045	0.018
Copper	0.195	0.103
Lead	0.015	0.013
Nickel	0.197	0.130
Zinc	0.150	0.062
TTO	0.066	0.035
Oil and grease(1)	2.060	1.236

(1) For alternate monitoring

Table 53 Cold Rolling Spent Lubricant

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy cold rolled	nds per 1,000,000 opper or copper
Chromium	0.166	0.068
Copper	0.720	0.379
Lead	0.056	0.049
Nickel	0.727	0.481
Zinc	0.553	0.231
TTO	0.246	0.128
Oil and grease(1)	7.580	4.548

(1) For alternate monitoring

Table 54
Drawing Spent Lubricant(1)

Diu	mg spent Businea	111(1)
	PSES	
	Maximum for any 1 day	Maximum for monthly aver- age
Pollutant or pollutant property		nds per 1,000,000 of copper or copper
Chromium	0.037	0.015
Copper	0.161	0.085
Lead	0.012	0.011
Nickel	0.163	0.107
Zinc	0.124	0.051
TTO	0.055	0.028
Oil and grease(2)	1.700	1.020

⁽¹⁾ These standards are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off–site for disposal or are otherwise not discharged at the copper forming site, these standards are neither applicable nor allowable.

(2) For alternate monitoring

Table 55 Solution Heat Treatment

Solution Heat Heatment		
	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy heat treated	
Chromium	0.284	0.116
Copper	1.227	0.646
Lead	0.096	0.083
Nickel	1.240	0.820
Zinc	0.943	0.394
TTO	0.419	0.219
Oil and grease ⁽¹⁾	12.920	7.752

(1) For alternate monitoring

Table 56 Extrusion Heat Treatment

Entrapion 110m 110minon		
	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy heat treated	
Chromium	0.00088	0.00036
Copper	0.0030	0.0020
Lead	0.00030	0.00026
Nickel	0.0030	0.0020
Zinc	0.0020	0.0010
TTO	0.0010	0.00068
Oil and grease(1)	0.040	0.024

(1) For alternate monitoring

Table 57 Annealing With Water

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy annealed w	
Chromium	0.545	0.223
Copper	2.356	1.240
Lead	0.186	0.161
Nickel	2.380	1.574
Zinc	1.810	0.756
TTO	0.806	0.421
Oil and grease(1)	24.800	14.880

(1) For alternate monitoring

Table 58 Annealing With Oil

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy annealed w	
Copper	0	0
Lead	0	0
Nickel	0	0
Zinc	0	0
TTO	0	0
Oil and grease(1)	0	0

(1) For alternate monitoring

Table 59 Alkaline Cleaning Rinse

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy alkaline clea	pper or copper
Chromium	1.854	0.758
Copper	8.006	4.214
Lead	0.632	0.547
Nickel	8.090	5.351
Zinc	6.152	2.570
TTO	2.739	1.432
Oil and grease(1)	84.280	50.568

(1) For alternate monitoring

Table 60 Alkaline Cleaning Rinse For Forged Parts

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy alkaline cle	
Chromium	5.562	2.275
Copper	24.019	12.642
Lead	1.896	1.643
Nickel	24.272	16.055
Zinc	18.457	7.711
TTO	8.217	4.298
Oil and grease(1)	252.840	151.704

(1) For alternate monitoring

Table 61 Alkaline Cleaning Bath

	PSES	<u> </u>
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of co alloy alkaline cle	opper or copper
Chromium	0.020	0.0084
Copper	0.088	0.046
Lead	0.0070	0.0060
Nickel	0.089	0.059
Zinc	0.068	0.028
TTO	0.030	0.015
Oil and grease(1)	0.93	0.56

⁽¹⁾ For alternate monitoring

Table 62 Pickling Rinse

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pound off–pounds) of co alloy pickled	ds per 1,000,000 opper or copper
Chromium	0.574	0.235
Copper	2.481	1.306
Lead	0.195	0.169
Nickel	2.507	1.658
Zinc	1.906	0.796
TTO	0.848	0.444
Oil and grease	26.120	15.672

⁽¹⁾ For alternate monitoring

Table 63
Pickling Rinse For Forged Parts

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pound off-pounds) of co alloy forged parts	opper or copper
Chromium	1.723	0.705
Copper	7.444	3.918
Lead	0.587	0.509
Nickel	7.522	4.975
Zinc	5.720	2.389
TTO	2.546	1.332
Oil and grease(1)	78.360	47.016

⁽¹⁾ For alternate monitoring

Table 64 Pickling Bath

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of co alloy pickled	
Chromium	0.051	0.020
Copper	0.220	0.116
Lead	0.017	0.015
Nickel	0.222	0.147
Zinc	0.169	0.070
TTO	0.075	0.039
Oil and grease(1)	2.320	1.392

⁽¹⁾ For alternate monitoring

Table 65 Pickling Fume Scrubber

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of c alloy pickled	ds per 1,000,000 opper or copper
Chromium	0.275	0.112
Copper	1.189	0.626
Lead	0.093	0.081
Nickel	1.201	0.795
Zinc	0.913	0.381
TTO	0.406	0.212
Oil and grease(1)	12.520	7.512

⁽¹⁾ For alternate monitoring

Table 66 Tumbling or Burnishing

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy tumbled or	
Chromium	0.256	0.104
Copper	1.107	0.583
Lead	0.087	0.075
Nickel	1.119	0.740
Zinc	0.851	0.355
TTO	0.378	0.198
Oil and grease(1)	11.660	6.996

⁽¹⁾ For alternate monitoring

Table 67 Surface Coating

Burrace Coating		
	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of calloy surface coa	opper or copper
Chromium	0.326	0.133
Copper	1.411	0.743
Lead	0.111	0.096
Nickel	1.426	0.943
Zinc	1.084	0.453
TTO	0.482	0.252
Oil and grease(1)	14.860	8.916

⁽¹⁾ For alternate monitoring

Table 68 Miscellaneous Waste Streams

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy formed	nds per 1,000,000 copper or copper
Chromium	0.009	0.003
Copper	0.041	0.021
Lead	0.003	0.002
Nickel	0.041	0.027
Zinc	0.031	0.013
TTO	0.014	0.007
Oil and grease(1)	0.436	0.261

(1) For alternate monitoring **History:** Cr. Register, May, 1989, No. 401, eff. 6–1–89.

NR 253.15 Pretreatment standards for new **sources.** Except as provided in s. NR 211.13, any existing [new] source subject to this subchapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSNS:

Table 69 Hot Rolling Spent Lubricant

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds pounds) of copper of rolled	
Chromium	0.038	0.015
Copper	0.131	0.062
Lead	0.010	0.0092
Nickel	0.056	0.038
Zinc	0.105	0.043
TTO	0.035	0.035
Oil and grease(1)	1.030	1.030

⁽¹⁾ For alternate monitoring

Table 70 Cold Rolling Spent Lubricant

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of c alloy cold rolled	
Chromium	0.140	0.056
Copper	0.485	0.231
Lead	0.037	0.034
Nickel	0.208	0.140
Zinc	0.386	0.159
TTO	0.128	0.128
Oil and grease(1)	3.790	3.790

⁽¹⁾ For alternate monitoring

Table 71 Drawing Spent Lubricant(1)

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of c alloy drawn	
Chromium	0.031	0.012
Copper	0.108	0.051
Lead	0.0085	0.0076
Nickel	0.046	0.031
Zinc	0.086	0.035
TTO	0.028	0.028
Oil and grease(2)	0.850	0.850

⁽¹⁾ These standards are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these standards are neither applicable nor allowable.

⁽²⁾ For alternate monitoring

Table 72 Solution Heat Treatment

5010	tion ricat freatmen	ıı
	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy heat treated	
Chromium	0.239	0.096
Copper	0.826	0.394
Lead	0.064	0.058
Nickel	0.355	0.239
Zinc	0.658	0.271
TTO	0.219	0.219
Oil and grease ⁽¹⁾	6.460	6.460

(1) For alternate monitoring

Table 73
Extrusion Heat Treatment

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of c alloy heat treated	
Chromium	0.00074	0.00030
Copper	0.0020	0.0010
Lead	0.00020	0.00018
Nickel	0.0010	0.00074
Zinc	0.0020	0.00084
TTO	0.00068	0.00068
Oil and grease ⁽¹⁾	0.020	0.020

(1) For alternate monitoring

Table 74 Annealing With Water

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of c alloy annealed w	
Chromium	0.458	0.186
Copper	1.587	0.756
Lead	0.124	0.111
Nickel	0.682	0.458
Zinc	1.264	0.520
TTO	0.421	0.421
Oil and grease ⁽¹⁾	12.400	12.400

(1) For alternate monitoring

Table 75 Annealing With Oil

	6	
	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil	
Chromium	0	0
Copper	0	0
Lead	0	0
Nickel	0	0
Zinc	0	0
TTO	0	0
Oil and grease ⁽¹⁾	0	0

(1) For alternate monitoring

Table 76 Alkaline Cleaning Rinse

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy alkaline cle	
Chromium	1.559	0.632
Copper	5.393	2.570
Lead	0.421	0.379
Nickel	2.317	1.559
Zinc	4.298	1.769
TTO	1.432	1.432
Oil and grease ⁽¹⁾	42.140	42.140

(1) For alternate monitoring

Table 77
Alkaline Cleaning Rinse For Forged Parts

	PSNS	·
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy alkaline cle	
Chromium	4.677	1.896
Copper	16.181	7.711
Lead	1.264	1.137
Nickel	6.953	4.677
Zinc	12.894	5.309
TTO	4.298	4.298
Oil and grease ⁽¹⁾	126.420	126.420

(1) For alternate monitoring

Table 78 Alkaline Cleaning Bath

Alkannic Cicaning Datii			
	PSNS		
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off–kg (poun off–pounds) of c alloy alkaline cle		
Chromium	0.017	0.0070	
Copper	0.059	0.028	
Lead	0.0046	0.0042	
Nickel	0.025	0.017	
Zinc	0.047	0.019	
TTO	0.015	0.015	
Oil and grease ⁽¹⁾	0.46	0.46	

⁽¹⁾ For alternate monitoring

Table 79 Pickling Rinse

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy pickled	ds per 1,000,000 opper or copper
Chromium	0.216	0.087
Copper	0.748	0.356
Lead	0.058	0.052
Nickel	0.321	0.216
Zinc	0.596	0.245
TTO	0.198	0.198
Oil and grease ⁽¹⁾	5.850	5.850

⁽¹⁾ For alternate monitoring

Table 80 Pickling Rinse For Forged Parts

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of c alloy forged part	opper or copper
Chromium	0.649	0.263
Copper	2.246	1.070
Lead	0.175	0.157
Nickel	0.965	0.649
Zinc	1.790	0.737
TTO	0.596	0.596
Oil and grease ⁽¹⁾	17.550	17.550

⁽¹⁾ For alternate monitoring

Table 81 Pickling Bath

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy pickled	nds per 1,000,000 opper or copper
Chromium	0.042	0.017
Copper	0.148	0.070
Lead	0.011	0.010
Nickel	0.063	0.042
Zinc	0.118	0.048
TTO	0.039	0.039
Oil and grease ⁽¹⁾	1.160	1.160

⁽¹⁾ For alternate monitoring

Table 82 Pickling Fume Scrubber

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of co alloy pickled	
Chromium	0.231	0.093
Copper	0.801	0.381
Lead	0.062	0.056
Nickel	0.344	0.231
Zinc	0.638	0.262
TTO	0.212	0.212
Oil and grease ⁽¹⁾	6.260	6.260

⁽¹⁾ For alternate monitoring

Table 83 Tumbling or Burnishing

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy tumbled or	
Chromium	0.215	0.087
Copper	0.746	0.355
Lead	0.058	0.052
Nickel	0.320	0.215
Zinc	0.594	0.244
TTO	0.198	0.198
Oil and grease ⁽¹⁾	5.830	5.830

⁽¹⁾ For alternate monitoring

Table 84 Surface Coating

Surface Counting		
	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy surface coa	
Chromium	0.274	0.111
Copper	0.951	0.453
Lead	0.074	0.066
Nickel	0.408	0.274
Zinc	0.757	0.312
TTO	0.252	0.252
Oil and grease ⁽¹⁾	7.430	7.430

⁽¹⁾ For alternate monitoring

Table 85 Miscellaneous Waste Streams

-	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy formed	
Chromium	0.008	0.003
Copper	0.027	0.013
Lead	0.0021	0.0019
Nickel	0.011	0.008
Zinc	0.022	0.009
TTO	0.007	0.007
Oil and grease ⁽¹⁾	0.218	0.218

(1) For alternate monitoring **History:** Cr. Register, May, 1989, No. 401, eff. 6–1–89.

State Code	Corresponding Federal Regulation	
s. NR 205.03	40 CFR 401.11	
s. NR 205.04	40 CFR 401.11	
ch. NR 211	40 CFR Part 403	
s. NR 211.03	40 CFR 403.03	
s. NR 211.13	40 CFR 403.7	
s. NR 211.14	40 CFR 403.13	
ch. NR 253	40 CFR Part 468	
ch. NR 256	40 CFR Part 464	